宣城晶瑞新材料有限公司

addree: qilin road,xuan zhou economic development zone,xuan cheng city,anhui province,China 电话(Tel):0563-2062263 传真(Fax):0571-81131920

Material Safety Data Sheet

Section 1: Chemical Product and Company Identification

Product Name: Nanometer magnesium oxide

Catalog Codes: SLM2716, SLM4093

CAS#: 1309-48-4 **RTECS**: OM3850000

TSCA: TSCA 8(b) inventory: Magnesium oxide

CI#: Not available.

Synonym: Magnesia; Calcined Brucite; Magnesium Oxide, Heavy Powder

Chemical Name: Magnesium Oxide

Chemical Formula: MgO

Manufacturer: Hang Zhou Wan Jing New Material Co, Ltd

Address: Innovation Park No.39 Xiangyuan Road Gongshu District Hangzhou Zhejiang China

Telephone: 0571-88920936, 85968971

Section 2: Composition and Information on Ingredients

Composition:

Name CAS # % by Weight
Nanometer magnesium oxide 1309-48-4 100

Toxicological Data on Ingredients: Not applicable.

Section 3: Hazards Identification

Potential Acute Health Effects: Slightly hazardous in case of skin contact (irritant), of eye contact (irritant), of ingestion, of inhalation.

Potential Chronic Health Effects:

CARCINOGENIC EFFECTS: Not available.

MUTAGENIC EFFECTS: Not available.

TERATOGENIC EFFECTS: Not available.

DEVELOPMENTAL TOXICITY: Not available.

Repeated or prolonged exposure is not known to aggravate medical condition.

Section 4: First Aid Measures

Eye Contact:

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. WARM water MUST be used. Get medical attention if irritation occurs.

Skin Contact: Wash with soap and water. Cover the irritated skin with an emollient. Get medical attention if irritation develops.

Serious Skin Contact: Not available.

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Serious Inhalation: Not available.

Ingestion:

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband.

Serious Ingestion: Not available.

Section 5: Fire and Explosion Data

Flammability of the Product: Non-flammable. **Auto-Ignition Temperature:** Not applicable.

Flash Points: Not applicable.

Flammable Limits: Not applicable.

Products of Combustion: Not available.

Fire Hazards in Presence of Various Substances: Not applicable.

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

Fire Fighting Media and Instructions: Not applicable.

Special Remarks on Fire Hazards:

Magnesium Oxide may ignite and explode when heated with sublimed sulfur, magesium powder, or aluminum powder.

It reacts violently with interhalogens (bromine pentafluoride, chlorine trifluoride) and produces flame. When combined with phosphorus pentachloride, it incandesces.

Special Remarks on Explosion Hazards:

Magnesium Oxide may ignite and explode when heated with sublimed sulfur, magesium powder, or aluminum powder.

Section 6: Accidental Release Measures

Small Spill:

Use appropriate tools to put the spilled solid in a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and dispose of according to local and regional authority requirements.

Large Spill:

Use a shovel to put the material into a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

Section 7: Handling and Storage

Precautions: Do not breathe dust. Keep away from incompatibles such as oxidizing agents, acids.

Storage:

Moisture Sensitive. Air Sensitive. Keep container tightly closed. Keep container in a cool, well-ventilated area.

Do not store above 24°C (75.2°F).

Section 8: Exposure Controls/Personal Protection

Engineering Controls:

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

Personal Protection: Safety glasses. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent.

Gloves.

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Dust respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits:

TWA: 10 (mg/m3) from ACGIH (TLV) [United States] Inhalation Total.

TWA: 4 STEL: 10 (mg/m3) [United Kingdom (UK)] Inhalation Respirable.

TWA: 15 (mg/m3) from OSHA (PEL) [United States] Inhalation Total.

TWA: 10 (mg/m3) [United Kingdom (UK)] Total. Consult local authorities for acceptable exposure limits.

Section 9: Physical and Chemical Properties

Physical state and appearance: Solid. (Powdered solid.)

Odor: Odorless. **Taste:** Not available.

Molecular Weight: 40.3 g/mole

Color: White.

pH (1% soln/water): Not available.
Boiling Point: 3600°C (6512°F)
Melting Point: 2800°C (5072°F)
Critical Temperature: Not available.

Specific Gravity: 3.58 @ 25 C (Water = 1)

Vapor Pressure: Not applicable.
Vapor Density: Not available.
Volatility: Not available.

Odor Threshold: Not available.

Water/Oil Dist. Coeff.: Not available.

lonicity (in Water): Not available.

Dispersion Properties: Not available.

Solubility:

Very slightly soluble in cold water.

Soluble in dilute acids and ammonium salt solutions.

Insoluble in alcohol.

Section 10: Stability and Reactivity Data

Stability: The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Incompatible materials, moisture, air.

Incompatibility with various substances: Reactive with oxidizing agents, acids.

Corrosivity: Non-corrosive in presence of glass.

Special Remarks on Reactivity:

Reacts violently with CIF3 (Chlorine Trifluoride) and PCI5 (Phosphorous Pentachloride).

Hygroscopic. Air Sensitrive. Readily absorbs moisture and carbon dioxide when exposed to air.

Hydrates slowly

in contact with moisture.

Takes up carbon dioxide and water from the air. This happens more readily for the light form vs. the heavy form.

Slight alkaline reaction to water.

Special Remarks on Corrosivity: Not available.

Polymerization: Will not occur.

Section 11: Toxicological Information

Routes of Entry: Inhalation. Ingestion.

Toxicity to Animals: LD50: Not available.

LC50: Not available.

Chronic Effects on Humans: Not available.

Other Toxic Effects on Humans: Slightly hazardous in case of skin contact (irritant), of

ingestion, of inhalation.

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans: May cause cancer (tumorigenic) based

on animal data. No human data

found.

Special Remarks on other Toxic Effects on Humans:

Acute Potential Health Effects:

Skin: Mild Alkali. May cause skin irritation. Eyes: Mild Alkali. May cause eye irritation.

Inhalation: May cause respiratory tract irritation.

Ingestion: May cause gastrointestinal tract irritation with nausea, vomiting, and diarrhea.

Chronic Potential Health Effects:

Inhalation: Repeated or prolonged exposure may result in Metal Fume Fever. Metal Fume

Fever is a flu-like condition consisting of fever, chills, sweating, aches, pains, cough,

weakness, headache, nausea, vomiting, and breathing difficulty. There is no permanent ill-effect. Metal Fume Fever resulting from Magnesiuim Oxide fumes has reportedly occurred in foundry workers. Repeated or prolonged exposure may also affect the blood and brain based on animal data. No human data found

Section 12: Ecological Information

Ecotoxicity: May cause alkalinization of water rendering it inhospitable to aquatic life.

BOD5 and COD: Not available. **Products of Biodegradation:**

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The product itself and its products of degradation are not toxic.

Special Remarks on the Products of Biodegradation: Not available.

Section 13: Disposal Considerations

Waste Disposal:

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

Section 14: Transport Information

DOT Classification: Not a DOT controlled material (United States).

Identification: Not applicable.

Special Provisions for Transport: Not applicable.

Section 15: Other Regulatory Information

Federal and State Regulations:

Illinois toxic substances disclosure to employee act: Magnesium oxide

Rhode Island RTK hazardous substances: Magnesium oxide

Pennsylvania RTK: Magnesium oxide

Minnesota: Magnesium oxide

Massachusetts RTK: Magnesium oxide

New Jersey: Magnesium oxide

California Director's List of Hazardous Substances: Magnesium oxide

TSCA 8(b) inventory: Magnesium oxide

Other Regulations: EINECS: This product is on the European Inventory of Existing

Commercial Chemical Substances.

Other Classifications:

WHMIS (Canada): Not controlled under WHMIS (Canada).

DSCL (EEC):

This product is not classified according

to the EU regulations.

Not applicable.

HMIS (U.S.A.):

Health Hazard: 1 Fire Hazard: 0 Reactivity: 0

Personal Protection: $\boldsymbol{\Xi}$

National Fire Protection Association (U.S.A.):

Health: 1

Flammability: 0
Reactivity: 0
Specific hazard:

Protective Equipment:

Gloves.

Lab coat.

Dust respirator. Be sure to use an approved/certified respirator or equivalent.
Safety glasses.

Section 16: Other Information

References: Not available.

Other Special Considerations: Not available.

Created: 10/10/2006